



## SUPER CLAMPS (W1)

### FEATURES & BENEFITS

- Heavy Duty
- High Tensile Strength
- Easy Assembly
- Reliable, Durable & Effective
- Bevelled Edges protect Hoses

### APPLICATIONS

- Agricultural Market Segments
- Waste Water Extraction
- Mining and Quarrying Equipment

### TECHNICAL SPECIFICATION

- 33 Sizes 17-19mm to 240-252mm
- Carbon Steel, Zinc Plated & White Zinc Plated
- 8.8 Grade Steel nut and T-Bolt
- Pressure: 3 to 48 Bar
- Torque 4.5 to 50 Nm

### CARBON STEEL, WHITE ZINC PLATED

Product Code	Size
SC17-19-GOLD	17mm-19mm
SC20-22-GOLD	20mm-22mm
SC23-25-GOLD	23mm-25mm
SC26-28-GOLD	26mm-28mm
SC29-31-GOLD	29mm-31mm
SC32-35-GOLD	32mm-35mm
SC36-39-GOLD	36mm-39mm
SC40-43-GOLD	40mm-43mm
SC44-47-GOLD	44mm-47mm
SC48-51-GOLD	48mm-51mm
SC52-55-GOLD	52mm-55mm
SC56-59-GOLD	56mm-59mm
SC60-63-GOLD	60mm-63mm
SC64-67-GOLD	64mm-67mm
SC68-73-GOLD	68mm-73mm
SC74-79-GOLD	74mm-79mm
SC80-85-GOLD	80mm-85mm
SC86-91-GOLD	86mm-91mm
SC92-97-GOLD	92mm-97mm
SC98-103-GOLD	98mm-103mm
SC104-112-GOLD	104mm-112mm
SC113-121-GOLD	113mm-121mm
SC122-130-GOLD	122mm-130mm
SC131-139-GOLD	131mm-139mm
SC140-148-GOLD	140mm-148mm
SC149-161-GOLD	149mm-161mm
SC162-174-GOLD	162mm-174mm
SC175-187-GOLD	175mm-187mm
SC188-200-GOLD	188mm-200mm
SC201-213-GOLD	201mm-213mm
SC214-226-GOLD	214mm-226mm
SC227-239-GOLD	227mm-239mm
SC240-252-GOLD	240mm-252mm



## SUPRA FERRITIC CLAMPS (W2)

### FEATURES & BENEFITS

- Heavy Duty
- High Tensile Strength
- Easy Assembly
- Reliable
- Durable & Effective
- Bevelled Edges protect Hoses

### APPLICATIONS

- Agricultural Market Segments
- Waste Water Extraction
- Mining and Quarrying Equipment
- Low Pressure Connections

### TECHNICAL SPECIFICATION

- 36 Sizes 17-19mm to 240-252mm
- 304 Stainless Steel
- Strengthened Bolt: Zinc Plated Mild Steel
- Pressure: 3 to 48 Bar
- Torque 4.5 to 50 Nm
- Complies fully with the RoHs Directive EU 20032/95/EC (1 July)

### 304 STAINLESS STEEL

Product Code	Size
SC17-19-SUF	17mm-19mm
SC19-21-SUF	19mm-21mm
SC21-23-SUF	21mm-23mm
SC23-25-SUF	23mm-25mm
SC25-27-SUF	25mm-27mm
SC27-29-SUF	27mm-29mm
SC29-31-SUF	29mm-31mm
SC31-34-SUF	31mm-34mm
SC34-37-SUF	34mm-37mm
SC37-40-SUF	37mm-40mm
SC40-43-SUF	40mm-43mm
SC43-47-SUF	43mm-47mm
SC47-51-SUF	47mm-51mm
SC51-55-SUF	51mm-55mm
SC55-59-SUF	55mm-59mm
SC59-63-SUF	59mm-63mm
SC63-68-SUF	63mm-68mm
SC68-73-SUF	68mm-73mm
SC73-79-SUF	73mm-79mm
SC79-85-SUF	79mm-85mm
SC85-91-SUF	85mm-91mm
SC91-97-SUF	91mm-97mm
SC97-104-SUF	97mm-104mm
SC104-112-SUF	104mm-112mm
SC112-121-SUF	112mm-121mm
SC121-130-SUF	121mm-130mm
SC130-140-SUF	130mm-140mm
SC140-150-SUF	140mm-150mm
SC150-162-SUF	150mm-162mm
SC162-174-SUF	162mm-174mm
SC174-187-SUF	174mm-187mm
SC187-200-SUF	187mm-200mm
SC200-213-SUF	200mm-213mm
SC213-226-SUF	213mm-226mm
SC226-239-SUF	226mm-239mm
SC239-252-SUF	239mm-252mm





**COMPLETE AISI 302  
STAINLESS STEEL**

Product Code	Size
SC17-19-SS	17mm-19mm
SC19-21-SS	19mm-21mm
SC21-23-SS	21mm-23mm
SC23-25-SS	23mm-25mm
SC25-27-SS	25mm-27mm
SC27-29-SS	27mm-29mm
SC29-31-SS	29mm-31mm
SC31-34-SS	31mm-34mm
SC34-37-SS	34mm-37mm
SC37-40-SS	37mm-40mm
SC40-43-SS	40mm-43mm
SC43-47-SS	43mm-47mm
SC47-51-SS	47mm-51mm
SC51-55-SS	51mm-55mm
SC55-59-SS	55mm-59mm
SC59-63-SS	59mm-63mm
SC63-68-SS	63mm-68mm
SC68-73-SS	68mm-73mm
SC73-79-SS	73mm-79mm
SC79-85-SS	79mm-85mm
SC85-91-SS	85mm-91mm
SC91-97-SS	91mm-97mm
SC97-104-SS	97mm-104mm
SC104-112-SS	104mm-112mm
SC112-121-SS	112mm-121mm
SC121-130-SS	121mm-130mm
SC130-140-SS	130mm-140mm
SC140-150-SS	140mm-150mm
SC150-162-SS	150mm-162mm
SC162-174-SS	162mm-174mm
SC174-187-SS	174mm-187mm
SC187-200-SS	187mm-200mm
SC200-213-SS	200mm-213mm
SC213-226-SS	213mm-226mm
SC226-239-SS	226mm-239mm
SC239-252-SS	239mm-252mm

**SUPRA CLAMPS (W4)**

**FEATURES & BENEFITS**

- Heavy Duty
- High Corrosion Resistance
- Easy to fit without disconnecting the Hose
- Swivelling Bridge
- Bevelled Edges protect Hoses

**APPLICATIONS**

- Low Pressure Marine
- Food Processing
- Industrial Applications where AISI 302 Stainless Steel is specified

**TECHNICAL SPECIFICATION**

- 36 Sizes 17-19mm to 240-252mm
- Full 304 Stainless Steel
- DIN 1.4301 Standard
- Pressure: 3 to 40 Bar
- Torque 10 to 50 Nm
- Complies fully with the RoHs Directive EU 20032/95/EC (1 July)

**SUMMARY**

**These Mikalor clamps** offers a cost effective easy to use and safe method of clamping fittings in your hose assembly.

It is the market leader in Europe because of its quality and reliability and Action-Sealtite offer the largest selections at the most competitive prices.

