

Hose Clamps: Roman Seliger



Technical Specification

- Sizes: 30mm - 33mm to 118mm - 122mm
- Aluminium as standard, Brass and Stainless Steel also available
- In accordance with DIN 2817
- Incorporates a lip, which is designed to engage behind an annular security collar on the hose stem
- For use up to 16 Bar



Use in conjunction with male & female inserts to DIN2817

Features & Benefits

- Streamline design
- Prevents hose 'blow off'
- Easy to fit
- Reusable

Applications

- Petrochemicals
- Foodstuffs
- Pharmaceuticals
- Blast furnaces
- Liquefied gas
- Aviation fuelling

Code	Hose OD	Material
Roman Seliger Safety Clamp		
RS19X6-AL	30mm - 33mm - Hose OD	Aluminium
RS25X6-AL	36mm - 39mm - Hose OD	Aluminium
RS25X8-AL	40mm - 43mm - Hose OD	Aluminium
RS32X6-AL	43mm - 46mm - Hose OD	Aluminium
RS38X6.5-AL	50mm - 52mm - Hose OD	Aluminium
RS38X8-AL	53mm - 56mm - Hose OD	Aluminium
RS38X10-AL	57mm - 60mm - Hose OD	Aluminium
RS45X7-AL	58mm - 61mm - Hose OD	Aluminium
RS50X8-AL	64mm - 67mm - Hose OD	Aluminium
RS50X10-AL	69mm - 71mm - Hose OD	Aluminium
RS75X8-AL	89mm - 93mm - Hose OD	Aluminium
RS80X10-AL	99mm - 102mm - Hose OD	Aluminium
RS100X8-AL	114mm - 119mm - Hose OD	Aluminium
RS100X10-AL	118mm - 122mm - Hose OD	Aluminium