

Air Pressure Fittings: Ludeke Universal Fittings

LÜDECKE



Technical Specification

- Malleable Iron with Zinc Plated finish
- Sizes: 3/8" to 1"
- Working pressure up to 10 PN bar
- Hose End, Female Threaded Adaptor & Male Threaded Adaptor
- Thread NPT
- Lug Distance 41mm

Features & Benefits

- Locking head conforms to American standard
- Safety lock pin
- Hose stem security collar prevents hose blow off with HP clamps
- Quick action
- Safety coupling

Applications

- For medium to high pressure compressed air applications
- Oil refineries
- Chemical plants
- Offshore rigs
- Industrial applications

Code	Size	Thread Type	Connection	Material	Pressure BAR	Pressure PSI	Seal Type
Ludecke Female Claw Coupling							
UF037-G	3/8"	NPT	Female Thread	Malleable Iron	10	150	Nitrile Rubber
UF050-G	1/2"	NPT	Female Thread	Malleable Iron	10	150	Nitrile Rubber
UF075-G	3/4"	NPT	Female Thread	Malleable Iron	10	150	Nitrile Rubber
UF100-G	1"	NPT	Female Thread	Malleable Iron	10	150	Nitrile Rubber
Ludecke Universal Hose Claw Coupling							
UH037-G	3/8"	NA	Hose Tail	Malleable Iron	10	150	Nitrile Rubber
UH050-G	1/2"	NA	Hose Tail	Malleable Iron	10	150	Nitrile Rubber
UH075	3/4"	NA	Hose Tail	Malleable Iron	10	150	Nitrile Rubber
UH100	1"	NA	Hose Tail	Malleable Iron	10	150	Nitrile Rubber



Air Pressure Fittings: Ludeke Universal Fittings

Ludecke Universal Male Claw Coupling

UM037-G	3/8"	NPT	Male Thread	Malleable Iron	10	150	Nitrile Rubber
UM050	1/2"	NPT	Male Thread	Malleable Iron	10	150	Nitrile Rubber
UM075-G	3/4"	NPT	Male Thread	Malleable Iron	10	150	Nitrile Rubber
UM100-G	1"	NPT	Male Thread	Malleable Iron	10	150	Nitrile Rubber

Stainless Steel Available on Request

