

## Camlock Fittings: Gaskets



### Technical Specification

- Standard Gaskets for metallic couplings are BUNA Nitrile
- For Polypropylene Snaplock couplings, standard gaskets are Ribbed Santoprene
- Various materials are available including, Buna, EPDM, Viton, Teflon Buna, Teflon Viton, Neoprene
- FEP/Silicone fully encapsulated seals also available for hazardous chemicals

### Features & Benefits

- Suitable for Snaplock® & other brands of camlock
- Various materials available for any application
- Simple & easy to replace

### Applications

- Camlock fittings
- Please refer to our chemical compatibility chart

Code	Size	Material	Min Temperature	Max Temperature
<b>Nitrile Buna</b>				
050GSK-BU	3/4"	Nitrile Buna	-40	93
050GSK-NB	1"	Nitrile Buna	-40	93
125GSK-BU	1 1/4"	Nitrile Buna	-40	93
150GSK-BU	1 1/2"	Nitrile Buna	-40	93
200GSK-BU	2"	Nitrile Buna	-40	93
250GSK-BU	2 1/2"	Nitrile Buna	-40	93
300GSK-BU	3"	Nitrile Buna	-40	93
400GSK-BU	4"	Nitrile Buna	-40	93
500GSK-BU	5"	Nitrile Buna	-40	93
600GSK-BU	6"	Nitrile Buna	-40	93

## Camlock Fittings: Gaskets

Code	Size	Material	Min Temperature	Max Temperature
<b>EPDM</b>				
050GSK-EP	1/2"	EPDM	-30	149
075GSK-EP	3/4"	EPDM	-30	149
100GSK-EP	1"	EPDM	-30	149
125GSK-EP	1 1/4"	EPDM	-30	149
150GSK-EP	1 1/2"	EPDM	-30	149
200GSK-EP	2"	EPDM	-30	149
250GSK-EP	2 1/2"	EPDM	-30	149
300GSK-EP	3"	EPDM	-30	149
400GSK-EP	4"	EPDM	-30	149
600GSK-EP	6"	EPDM	-30	149
<b>Fully Encapsulated Silicone</b>				
050GSK-FEPSIL	1/2"	Fully Encapsulated Silicone	-60	205
075GSK-FEPSIL	3/4"	Fully Encapsulated Silicone	-60	205
100GSK-FEPSIL	1"	Fully Encapsulated Silicone	-60	205
125GSK-FEPSIL	1 1/4"	Fully Encapsulated Silicone	-60	205
150GSK-FEPSIL	1 1/2"	Fully Encapsulated Silicone	-60	205
200GSK-FEPSIL	2"	Fully Encapsulated Silicone	-60	205
250GSK-FEPSIL	2 1/2"	Fully Encapsulated Silicone	-60	205
300GSK-FEPSIL	3"	Fully Encapsulated Silicone	-60	205
400GSK-FEPSIL	4"	Fully Encapsulated Silicone	-60	205
<b>Neoprene Black</b>				
075GSK-NB	3/4"	Neoprene Black	-50	107
100GSK-NB	1"	Neoprene Black	-50	107
125GSK-NB	1 1/4"	Neoprene Black	-50	107
150GSK-NB	1 1/2"	Neoprene Black	-50	107
200GSK-NB	2"	Neoprene Black	-50	107
250GSK-NB	2 1/2"	Neoprene Black	-50	107
300GSK-NB	3"	Neoprene Black	-50	107
400GSK-NB	4"	Neoprene Black	-50	107



## Camlock Fittings: Gaskets

Code	Size	Material	Min Temperature	Max Temperature
<b>Teflon Buna</b>				
050GSK-TB	1/2"	Teflon Buna	-40	93
075GSK-TB	3/4"	Teflon Buna	-40	93
100GSK-TB	1"	Teflon Buna	-40	93
125GSK-TB	1 1/4"	Teflon Buna	-40	93
150GSK-TB	1 1/2"	Teflon Buna	-40	93
200GSK-TB	2"	Teflon Buna	-40	93
250GSK-TB	2 1/2"	Teflon Buna	-40	93
300GSK-TB	3"	Teflon Buna	-40	93
400GSK-TB	4"	Teflon Buna	-40	93
<b>Teflon Viton</b>				
050GSK-TV	1/2"	Teflon Viton	-40	200
075GSK-TV	3/4"	Teflon Viton	-40	200
100GSK-TV	1"	Teflon Viton	-40	200
125GSK-TV	1 1/4"	Teflon Viton	-40	200
150GSK-TV	1 1/2"	Teflon Viton	-40	200
200GSK-TV	2"	Teflon Viton	-40	200
250GSK-TV	2 1/2"	Teflon Viton	-40	200
300GSK-TV	3"	Teflon Viton	-40	200
400GSK-TV	4"	Teflon Viton	-40	200
<b>Viton (FKM)</b>				
050GSK-VA	1/2"	Viton (FKM)	-40	200
075GSK-VA	3/4"	Viton (FKM)	-40	200
100GSK-VA	1"	Viton (FKM)	-40	200
125GSK-VA	1 1/4"	Viton (FKM)	-40	200
150GSK-VA	1 1/2"	Viton (FKM)	-40	200
200GSK-VA	2"	Viton (FKM)	-40	200
250GSK-VA	2 1/2"	Viton (FKM)	-40	200
300GSK-VA	3"	Viton (FKM)	-40	200
400GSK-VA	4"	Viton (FKM)	-40	200
500GSK-VA	5"	Viton (FKM)	-40	200
600GSK-VA	6"	Viton (FKM)	-40	200



## Camlock Fittings: Gaskets

Code	Size	Material	Min Temperature	Max Temperature
<b>Ribbed Santoprene</b>				
075GSK-E	1/2 - 3/4"	Ribbed Santoprene	-50	150
100GSK-E	1"	Ribbed Santoprene	-50	150
125GSK-E	1 1/4"	Ribbed Santoprene	-50	150
150GSK-E	1 1/2"	Ribbed Santoprene	-50	150
200GSK-E	2"	Ribbed Santoprene	-50	150
300GSK-E	3"	Ribbed Santoprene	-50	150
400GSK-E	4"	Ribbed Santoprene	-50	150

*The measurement of gaskets is taken from the total outside diameter of the material.*

