

Quick Release Couplings: QuickBreak® ISO A



Technical Specification

- ISO7241 Series A
- Double shut-off with good flow characteristics
- Sizes: 1/4" to 1" (1 1/4" to 2" to Order)
- Working pressures up to 400 Bar (depending on material & size)
- Materials: Plated Steel
- Effective ball-locking system
- Sleeve lock if required
- Buna seals - Viton available on request



Features & Benefits

- Robust design
- Interchangeable with other fittings manufactured to ISO-A standard
- Quick & easy operation

Applications

- Agricultural
- Mobile
- Construction
- Hydraulic circuits

Code	Size	Material	Thread Type	Pressure BAR	Seal Type
ISO A Nipple - Female Thread					
QDA-N025PS-RPB	1/4"	Steel	BSPP	400	Buna Nitrile
QDA-N038PS-FB	3/8"	Steel	NPT	300	Buna Nitrile
QDA-N038PS-RPB	3/8"	Steel	BSPP	300	Buna Nitrile
QDA-N050PS-FB	1/2"	Steel	NPT	250	Buna Nitrile
QDA-N050PS-RPB	1/2"	Steel	BSPP	250	Buna Nitrile
QDA-N050PS-RPV	1/2"	Steel	BSPP	250	Viton/FKM
QDA-N075PS-RPB	3/4"	Steel	BSPP	250	Buna Nitrile
QDA-N100PS-RPB	1"	Steel	BSPP	230	Buna Nitrile

Quick Release Couplings: QuickBreak® ISO A

Code	Size	Material	Thread Type	Pressure BAR	Seal Type
ISO A Socket - Female Coupler by Female Thread					
QDA-S025PS-RPB	1/4"	Steel	BSPP	300	Buna Nitrile
QDA-S038PS-RPB	3/8"	Steel	BSPP	300	Buna Nitrile
QDA-S050PS-FB	1/2"	Steel	NPT	250	Buna Nitrile
QDA-S050PS-RPB	1/2"	Steel	BSPP	250	Buna Nitrile
QDA-S050PS-RPV	1/2"	Steel	BSPP	250	Viton/FKM
QDA-S075PS-RPB	3/4"	Steel	BSPP	250	Buna Nitrile
QDA-S100PS-RPB	1"	Steel	BSPP	207	Buna Nitrile

