

DIN Fittings: Roman Seliger Hose Fittings



Technical Specification

- Materials:
Clamps - Aluminium, Brass & Stainless Steel
Hose tails - Brass & Stainless Steel
- Sizes: 1/2" to 4" available
- Seal: Vulkolan
- Pressures: Brass & Stainless Steel - 25 Bar
Aluminium - 16 Bar
- Conforms to DIN 2817/EN14420-2

Features & Benefits

- Smooth tail protects hose
- Ribbed clamps ensure consistent safe retention of hose
- Collar for security
- Spare seals available on request

Applications

- Chemical
- Pharmaceutical
- Petrochemical
- Food and drink

Code	To Suit Hose OD	Thread Type	Material	Pressure BAR	Pressure PSI
Female Thread by Smooth Hose Tail					
RS100F-BR	1"	BSP	Brass	25	360
RS150F-BR	1 1/2"	BSP	Brass	25	360
RS200F-BR	2"	BSP	Brass	25	360
RS250F-BR	2 1/2"	BSP	Brass	25	360
Male Thread by Smooth Hose Tail					
RS100M-BR	1"	BSP	Brass	25	360
RS125M-BR	1 1/4"	BSP	Brass	25	360
RS150M-BR	1 1/2"	BSP	Brass	25	360
RS250M-BR	2 1/2"	BSP	Brass	25	360

Also available in Stainless Steel, Tin Plated Brass & ECTFE coated Stainless Steel



DIN Fittings: Roman Seliger Hose Fittings

Aluminium Safety Clamps

RS19X6-AL	30mm - 33mm	NA	Aluminium	NA	NA
RS25X6-AL	36mm - 39mm	NA	Aluminium	NA	NA
RS25X8-AL	40mm - 43mm	NA	Aluminium	NA	NA
RS32X6-AL	43mm - 46mm	NA	Aluminium	NA	NA
RS38X6.5-AL	50mm - 52mm	NA	Aluminium	NA	NA
RS38X8-AL	53mm - 56mm	NA	Aluminium	NA	NA
RS38X10-AL	57mm - 60mm	NA	Aluminium	NA	NA
RS45X7-AL	58mm - 61mm	NA	Aluminium	NA	NA
RS50X8-AL	64mm - 67mm	NA	Aluminium	NA	NA
RS50X10-AL	69mm - 71mm	NA	Aluminium	NA	NA
RS75X8-AL	89mm - 93mm	NA	Aluminium	NA	NA
RS80X10-AL	99mm - 102mm	NA	Aluminium	NA	NA
RS100X8-AL	114mm - 119mm	NA	Aluminium	NA	NA
RS100X10-AL	118mm - 122mm	NA	Aluminium	NA	NA

All clamps also available in Stainless Steel or Brass