

Ball Valves: Stainless Steel 2 Piece

Technical Specification

- Sizes: 1/4" - 2"
- Materials:
 - Body, Cap & Ball: A315 CF8M Stainless Steel
 - Handle & Locking Device: 430 Stainless Steel
 - Ball Seat, Joint Gasket, Thrust Washer & Stem Packing: PTFE
 - Stem: 316 Stainless Steel
 - Gland Nut, Stem Nut, Spring washer: 304 Stainless Steel
 - Handle Sleeve: Plastic
- Temperature: -10°C to 180°C
- Pressure: Up to 65 Bar



Features & Benefits

- Anti-blowout Stem
- Full Bore
- Locking Device

Applications

- Agricultural
- Water works (pumps)
- Irrigation
- Oils (certain fuels, diesel, hydraulic)
- Gases (natural & inert)
- Alcohol & Beer
- Pharmaceutical
- Foods

Part Number	Size	Connection	Thread	Material	Pressure		Seal
					Bar	PSI	
Stainless Steel Locking Lever Ball Valves							
BV025-SS	1/4"	Female Thread by Female Thread	BSP	Stainless Steel 316	65	940	PTFE
BV038-SS	3/8"	Female Thread by Female Thread	BSP	Stainless Steel 316	65	940	PTFE
BV050-SS	1/2"	Female Thread by Female Thread	BSP	Stainless Steel 316	65	940	PTFE
BV075-SS	3/4"	Female Thread by Female Thread	BSP	Stainless Steel 316	65	940	PTFE
BV100-SS	1"	Female Thread by Female Thread	BSP	Stainless Steel 316	65	940	PTFE
BV125-SS	1 1/4"	Female Thread by Female Thread	BSP	Stainless Steel 316	65	940	PTFE
BV150-SS	1 1/2"	Female Thread by Female Thread	BSP	Stainless Steel 316	65	940	PTFE
BV200-SS	2"	Female Thread by Female Thread	BSP	Stainless Steel 316	65	940	PTFE

