

Air Pressure Fittings: Whipchecks

Technical Specification



Model A & Whipcheck A

- 1/8" thick for hoses 1/2" (13mm to 1 1/4" (32mm) OD
- Length 540mm
- Breaking strain of 588kg
- Model A comes with a yellow plastic tag

Model B & Whipcheck B

- 1/4" for hoses 1 1/2" (40mm) to 3" (75mm) OD
- Length 965mm
- Breaking strain of 2350kg
- Model B comes with a yellow plastic tag



Features & Benefits

- Other materials available for special applications
- The galvanised steel cable prevents hose whip with fitted easily spring loaded loops

Applications

- Coal mining
- Sea water
- Petrochemical
- Compressed air

Code	Material	Size OD
MODEL-A	Galvanised Steel w/Tag	1/2" (13mm) - 1 1/4" (32mm)
MODEL-B	Galvanised Steel w/Tag	1 1/2" (40mm) - 3" (75mm)
WHIPCHECK A	Galvanised Steel	1/2" (13mm) - 1 1/4" (32mm)
WHIPCHECK A-10"	Galvanised Steel	1/2" (13mm) - 1 1/4" (32mm): 10" Long
WHIPCHECK A-12"	Galvanised Steel	1/2" (13mm) - 1 1/4" (32mm): 12" Long
WHIPCHECK A-SS	Stainless Steel 316	1/2" (13mm) - 1 1/4" (32mm)
WHIPCHECK B	Galvanised Steel	1 1/2" (40mm) - 3" (75mm)
WHIP1500-B-TOOL	Galvanised Steel	(Hose to Tool) 1.5m Long
WHIPCHECK B-SS	Stainless Steel 316	1 1/2" (40mm) - 3" (75mm)
WHIPCHECK C	Galvanised Steel	3" (76mm) - 6" (150mm)