



BALL VALVES

ECO Ball	Valves: 1, 2 &	3 Piece Su	mmary	146
ECO Ball	Valves in 316	Stainless S	Steel	147

ECO Ball Valves: 1, 2 & 3 Piece



FEATURES & BENEFITS

- Safety feature for operators
- Allows faster product transfer
- Security for product lines
- Screwed BSP Parallel
- Allows for full traceability

APPLICATIONS

- All Water Applications
- Certain Fuels, Diesel & Hydraulic
- Gases (Natural & Inert)
- All Food & Drink

TECHNICAL SPECIFICATION

- Sizes ½" to 2"
- Body, Bonnet, Ball, Stem, Gland & Lock Nut: 316 Stainless Steel
- Seat & Packing: PTFE

- Handle: 304 Stainless Steel
- Working Pressure: ½" to 2" 65 Bar
- Working temperature: -25 to +150°C
- CE approved 2014/68/EU
- Conform to PED97/23/EC

SUMMARY

General purpose Stainless Steel ball valves designed to be used in a multitude of different applications and industries. Stainless steel valves have a built in safety locking device so they can be locked in either the open or closed position.

ECO Ball Valves: 1, 2 & 3 Piece

ECO: 1 PIECE BALL VALVES IN 316 STAINLESS STEEL



Product Code	Nominal ins		Thread	Seal	Bore Type	Max Working Pressure Bar	PSI
Code	IIIS	mm	Tilleau	Seat	туре	Fressure Dai	ГЭІ
WBV050-1PC-SS	1/2	13	BSP	PTFE	Reduced Bore	65	1000
WBV075-1PC-SS	3/4	19	BSP	PTFE	Reduced Bore	65	1000
WBV100-1PC-SS	1	25	BSP	PTFE	Reduced Bore	65	1000
WBV125-1PC-SS	1 1/4	32	BSP	PTFE	Reduced Bore	65	1000
WBV150-1PC-SS	1 1/2	40	BSP	PTFE	Reduced Bore	65	1000
WBV200-1PC-SS	2	50	BSP	PTFE	Reduced Bore	65	1000

ECO: 2 PIECE BALL VALVES IN 316 STAINLESS STEEL



Product	roduct Nominal Size				Bore	Max Working	
Code	ins	mm	Thread	Seal	Туре	Pressure Bar	PSI
WBV050-2PC-SS	1/2	13	BSP	PTFE	Full Bore	65	1000
WBV075-2PC-SS	3/4	19	BSP	PTFE	Full Bore	65	1000
WBV100-2PC-SS	1	25	BSP	PTFE	Full Bore	65	1000
WBV125-2PC-SS	1 1/4	32	BSP	PTFE	Full Bore	65	1000
WBV150-2PC-SS	1 1/2	40	BSP	PTFE	Full Bore	65	1000
WBV200-2PC-SS	2	50	BSP	PTFE	Full Bore	65	1000

ECO: 3 PIECE BALL VALVES IN 316 STAINLESS STEEL



Product Code	Nominal Si	ze mm	Thread	Seal	Bore Type	Max Working Pressure Bar	PSI
Code	IIIS		Tilleau	Seat	туре	Fressure Dai	FOI
WBV050-3PC-SS	1/2	13	BSP	PTFE	Full Bore	65	1000
WBV075-3PC-SS	3/4	19	BSP	PTFE	Full Bore	65	1000
WBV100-3PC-SS	1	25	BSP	PTFE	Full Bore	65	1000
WBV125-3PC-SS	1 1/4	32	BSP	PTFE	Full Bore	65	1000
WBV150-3PC-SS	1 1/2	40	BSP	PTFE	Full Bore	65	1000
WBV200-3PC-SS	2	50	BSP	PTFE	Full Bore	65	1000

ECO T & L PORT BALL VALVES IN 316 STAINLESS STEEL



Product Code	Nominal ins	Size mm	Thread	Seal	Bore Type	Max Working Pressure Bar	PSI
WBV025-SS-3T	1/4	6	BSP	PTFE	Reduced Bore	65	1000
WBV0375-SS-3T	3/8	10	BSP	PTFE	Reduced Bore	65	1000
WBV050-SS-3T	1/2	13	BSP	PTFE	Reduced Bore	65	1000
WBV075-SS-3T	3/4	19	BSP	PTFE	Reduced Bore	65	1000
WBV100-SS-3T	1	25	BSP	PTFE	Reduced Bore	65	1000
WBV125-SS-3T	1 1/4	32	BSP	PTFE	Reduced Bore	65	1000
WBV150-SS-3T	1 1/2	40	BSP	PTFE	Reduced Bore	65	1000
WBV200-SS-3T	2	50	BSP	PTFE	Reduced Bore	65	1000
WBV025-SS-3L	1/4	6	BSP	PTFE	Reduced Bore	65	1000
WBV0375-SS-3L	3/8	10	BSP	PTFE	Reduced Bore	65	1000
WBV050-SS-3L	1/2	13	BSP	PTFE	Reduced Bore	65	1000
WBV075-SS-3L	3/4	19	BSP	PTFE	Reduced Bore	65	1000
WBV100-SS-3L	1	25	BSP	PTFE	Reduced Bore	65	1000
WBV125-SS-3L	1 1/4	32	BSP	PTFE	Reduced Bore	65	1000
WBV150-SS-3L	1 1/2	40	BSP	PTFE	Reduced Bore	65	1000
WBV200-SS-3L	2	50	BSP	PTFE	Reduced Bore	65	1000