

Airline Fittings: TST 68 Series

Technical Specification



- Sizes: 10mm - 3/4"
- Materials:
 - Coupler Body & Sleeve: Nickel Plated Steel
 - Valve: Zinc Diecasting
 - Springs & Locking O-Ring: Stainless Steel
- Seal: Nitrile
- Pressures: 0 - 35 Bar
- Temperature: -20°C - +100°C
- Flow Capacity: NW - 8.5

Features & Benefits

- Straight-through flow
- Durable
- Interchangeable with Rectus 68, & Schrader Heavy Duty

Applications

- Plumbing
- Injection Moulding
- Washdown

Code	Series Product Type	Size	Connection	Material	Pressure BAR	Pressure PSI
Series 68 Couplers						
TS068DG13	Series 68 Couplers	1/4"	Female	Plated Steel	35	500
TS068EG17	Series 68 Couplers	3/8"	Male	Plated Steel	35	500
TS068DG17	Series 68 Couplers	3/8"	Female	Plated Steel	35	500
TS068EG21	Series 68 Couplers	1/2"	Male	Plated Steel	35	500
TS068DG21	Series 68 Couplers	1/2"	Female	Plated Steel	35	500
TS068EG26	Series 68 Couplers	3/4"	Male	Plated Steel	35	500
TS068DG26	Series 68 Couplers	3/4"	Female	Plated Steel	35	500
TS068HG10	Series 68 Couplers	10mm	Hosetail	Plated Steel	35	500
TS068HG13	Series 68 Couplers	13mm	Hosetail	Plated Steel	35	500
TS068HG19	Series 68 Couplers	19mm	Hosetail	Plated Steel	35	500

Airline Fittings: TST 68 Series

Code	Series Product Type	Size	Connection	Material	Pressure BAR	Pressure PSI
Series 68 Nipples						
TS068DU13	Series 68 Nipples	1/4"	Female	Plated Steel	35	500
TS068EU13	Series 68 Nipples	1/4"	Male	Plated Steel	35	500
TS068DU17	Series 68 Nipples	3/8"	Female	Plated Steel	35	500
TS068EU17	Series 68 Nipples	3/8"	Male	Plated Steel	35	500
TS068EU21	Series 68 Nipples	1/2"	Male	Plated Steel	35	500
TS068EU27	Series 68 Nipples	3/4"	Male	Plated Steel	35	500