

Ball Valves: Banjo Stubby Polypropylene

Technical Specification



- Sizes: 2" & 3"
- Ports: Standard or Full
- Material:
 - Body: Glass Reinforced Polypropylene
 - Bolts: Stainless Steel
- Thread: NPT (BSP available in some sizes)
- Ball Seat: PTFE
- Body Seal: Viton (Except 2" standard port: PTFE)
- Pressure ratings are dependant on operating temperatures

Features & Benefits

- Precision moulded
- Compact
- High chemical resistance
- Smooth operation
- Light weight

Applications

- Agriculture
- Agrochemicals
- Chemical Plants
- Fluid Processing

Part Number	Description	Max Pressure PSI	Pipe Size	Opening Thru Ball
2" Standard Port Stubby Valves				
VSF200	2" Male Adapter x 2" Female NPT	100	2"	1½"
VSMT200	2" Male NPT x 2" Female NPT	100	2"	1½"
VSFMT200	2" Male Adapter x 2" Male NPT	100	2"	1½"
VSFHB200	2" Male Adapter x 2" Hose Barb	100	2"	1½"
2" Full Port Stubby Valves				
VSMT204FP	2" Male NPT x 2" Female NPT	100	2"	2"
VSF204FP	2" Male Adapter x 2" Female NPT	100	2"	2"
VS204FP	2" Female NPT x 2" Female NPT	100	2"	2"
VSFMT204FP	2" Male Adapter x 2" Male NPT	100	2"	2"
VSFMT204HSFP	2" FP Male Adapter x 2" Male NPT w/ SS Ball, Stem & Handle	100	2"	2"

Ball Valves: Banjo Stubby Polypropylene

Part Number	Description	Max Pressure PSI	Pipe Size	Opening Thru Ball
3" Standard Port Stubby Valves				
VSMT300	3" Female NPT x 3" Male NPT	100	3"	2½"
VSF300	3" Female NPT x 3" Male Adapter	100	3"	2½"
VSFMT300	3" Male NPT x 3" Male Adapter	100	3"	2½"
3" Full Port Port Stubby Valves				
VSFMT300FP	3" FP Male Adapter x 3" Male NPT	100	3"	3"
3" Full Port Stubby Valves w/SS				
VSFMT300HSFP	3" FP Male Adapter x 3" Male NPT w/SS ball, Stem & Handle	100	3"	3"